

CEMBOND

NON-HAZARDOUS POLYMER-BASED RESIN (CONCENTRATE)

CemBond contains resin with exceptional adhesive qualities. It has been proven over the past couple of decades to be a reliable general-purpose adhesive for the building & decorative industry. It dispenses the need for hacking when plastering, tiling or painting onto smooth or friable surfaces. It can be used as an adhesive, a bonding liquid for friable surfaces, as a primer for PVA & acrylic paints, as a cement additive to improve adhesion, mixed with cement as a crack filler and mixed with propriety crack fillers to limit ghosting of filled spots when over coating with paint. It can be used in plaster mixes to improve the strength & integrity of the plaster & is invaluable for improving the adhesion of cement based decorative coatings to difficult surfaces.

SUITABLE SURFACES

Dry stack brickwork, breeze blocks, stock & face bricks, concrete, hard & clean bag wash, scratch plaster, previously painted surfaces, tiles etc.

FINISH

Translucent when dry.

APPLICATION

Brush-on, sponge-on or roll-on.

CURING

Bonding time: ± 1 hour. Initial set: ± 4 hours depending on weather. Needs to air cure for at least 12 hours.

PACKAGING

1, 5 & 20 litre containers.

COVERAGE

30m²/litre of concentrated CemBond mixed 1:5 with water per coat, depending on surface porosity.

APPEARANCE / COLOUR(S) Milky white liquid.



BENEFITS

- Eliminates hacking
- Sold undiluted, therefore offering a more economical choice. Must be diluted before use
 - Lime fast
 - Compatible with cement, lime, sand and gypsum
 - Dries translucent
 - Adheres to concrete, brick, tiles, cement, plaster and stone
 - Non-flammable



cnr Bosmansdam & Omuramba Roads Montague Gardens (021) 555 1034 cape@cemcrete.co.za

You Tube

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.



Manufacturers of Distinctive Decorative Coatings

Creating distinctive cement finishes as you are.