



**ICEMCRETE**<sup>®</sup>

Manufacturers of Distinctive Decorative Coatings

# CONCRETE PRIMER

MODIFIED LIQUID CEMENT PRIMER



# CONCRETE PRIMER

## MODIFIED LIQUID CEMENT PRIMER

Concrete Primer equalises the suction of a cement substrate by reducing the substrate's porosity, & ensures a good bond for subsequent products to be applied. To be used on wood floated (rough) & porous surfaces, ensuring a good bond onto the substrate. Dense, impervious surfaces should be ground to expose the surface pores & to create a relatively flat & level surface.

### SUITABLE SURFACES

Wood floated (rough) & porous floor surfaces.

### APPLICATION

Brush-on, sponge-on or roll-on.

### CURING

Needs to air cure for at least 12 hours.

### PACKAGING

Supplied in 1, 5 & 20 litre containers.

### COVERAGE

Varies depending on the surface porosity, but is approximately 5m<sup>2</sup> per litre.

### APPEARANCE / COLOUR(S)

Milky white liquid.



### BENEFITS

- It is used to equalise suction by reducing substrate porosity
- Ensures a good bond onto the substrate being coated
- The base polymer is slowly biodegradable



0860 CEMCRETE

info@cemcrete.co.za

www.cemcrete.co.za



## HEAD OFFICE

Showroom & Warehouse  
8 Telford Street  
Industria  
(011) 474 2415  
info@cemcrete.co.za

## GAUTENG

Johannesburg Showroom  
227 Jan Smuts Avenue  
Parktown North  
(011) 447 3149  
jsa@cemcrete.co.za

## Centurion Showroom & Warehouse

15 Coachmen's Park  
26 Jakaranda Street  
Centurion  
(012) 653 6808  
pretoria@cemcrete.co.za

## CAPE TOWN

Showroom & Warehouse  
Unit 3 Eagle Park  
cnr Bosmansdam & Omuramba Roads  
Montague Gardens  
(021) 555 1034  
cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.

**CEMCRETE**<sup>®</sup>

Manufacturers of Distinctive Decorative Coatings

Creating distinctive cement finishes  
as *unique* as you are.