



ICEMCRETE[®]

Manufacturers of Distinctive Decorative Coatings

EIFS

BASECOAT

COATING TO LEVEL OR REPAIR VERTICAL CONCRETE SURFACES

EIFS BaseCoat is a special mixture of various admixtures and Ordinary Portland Cement for repair of concrete and masonry, adhering and surfacing of EIFS insulation boards prior to applying Cemcrete's decorative coatings.

SUITABLE SURFACES
Interior or exterior wall surfaces and polystyrene.

APPLICATION
Trowel-on.

FINISH
Smooth.


THICKNESS
2 - 6mm.

CURING
Leave to dry for 48 hours.

PACKAGING
20kg bag.

COVERAGE
Approximately 3 - 4m² per 20kg if applied at a 3 - 4mm thickness.

APPEARANCE / COLOUR(S)
Grey powder.



01. ADHESIVE APPLICATION

Ideal for attaching polystyrene EIFS insulation boards or shaped architectural feature Segments of polystyrene to the interior or exterior of buildings and the subsequent hard surfacing of the former to take paint or plaster.

Apply the EIFS BaseCoat to the entire surface using a 6-10mm notched trowel. Press polystyrene EIFS insulation board firmly so as to flatten adhesive between substrate and board.

02. POLYSTYRENE OR FOAM APPLICATION

Ideal for coating polystyrene or foam and will harden the surface before applying paint or plaster.

Apply EIFS BaseCoat to a uniform thickness of about 2mm using a steel float. Immediately press fibre glass re-enforcing mesh into wet EIFS BaseCoat. Apply a second 2mm layer of EIFS BaseCoat and smooth the material with a trowel until the mesh is totally imbedded and the pattern of the mesh does not show through.

03. REPAIR MORTAR

Repair mortar for levelling, patching and filling masonry, concrete and plaster before painting, with or without a glass fibre reinforcing mesh. Not for floor repairs.

Apply to cleaned substrate to required thickness of no more than 6mm per coat using a steel trowel making sure material is to correct level.



BENEFITS

- Can be used as a base coat for levelling, patching & filling masonry, concrete & plaster before painting
- Can be used as an adhesive for adhering insulation board (polystyrene) or feature segments onto the interior or exterior of buildings
- Can be used as a leveller & filler for masonry, concrete or plaster surfaces

0860 CEMCRETE

info@cemcrete.co.za

www.cemcrete.co.za



HEAD OFFICE

Showroom & Warehouse
8 Telford Street
Industria
(011) 474 2415
info@cemcrete.co.za

GAUTENG

Johannesburg Showroom
227 Jan Smuts Avenue
Parktown North
(011) 447 3149
jsa@cemcrete.co.za

Centurion Showroom & Warehouse

15 Coachmen's Park
26 Jakaranda Street
Centurion
(012) 653 6808
pretoria@cemcrete.co.za

CAPE TOWN

Showroom & Warehouse
Unit 3 Eagle Park
cnr Bosmansdam & Omuramba Roads
Montague Gardens
(021) 555 1034
cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.

CEMCRETE[®]

Manufacturers of Distinctive Decorative Coatings

Creating distinctive cement finishes
as *unique* as you are.