

# CEMENT LINING FOR THATCH ROOFS

## **THATCHCRETE**

### CEMENT LINING FOR THATCH ROOFS

For creating a thin, reinforced, waterproof, fire resistant, cement lining to be applied directly onto the exterior of an old or new grass thatched roof. This lining is tough enough to resist mammals like baboons, vervet monkeys as well as birds from causing damage to the roof or entering the building.

SUITABLE SURFACES

Exterior of an old or new grass thatched roof.

FINISH Textured finish.

THICKNESS Approximately 4mm.

APPLICATION Brush-on.

CURING

Allow finished ThatchCrete work to air cure for 5 days.

PACKAGING 40kg bags.

**COVERAGE** 

5m<sup>2</sup> per 40kg bag depending on thickness of final work.

NOTE

Can be coated with CemWash which is available in 18 colours.







#### **BENEFITS**

- Applied directly onto the exterior of new or old grass thatched roofs
  - Not only offers a waterproof finish, but is resistant to fire as well
- Resistant to dismantling by mammals (such as baboons, etc) and birds



info@cemcrete.co.za www.cemcrete.co.za











#### **HEAD OFFICE**

Showroom & Warehouse & Telford Street Industria (011) 474 2415 info@cemcrete.co.za

#### **GAUTENG**

#### Johannesburg Showroom

227 Jan Smuts Avenue Parktown North (011) 447 3149 jsa@cemcrete.co.za

#### Centurion Showroom & Warehouse

15 Coachmen's Park 26 Jakaranda Street Centurion (012) 653 6808 pretoria@cemcrete.co.za

#### **CAPE TOWN**

#### Showroom & Warehouse

Unit 3 Eagle Park cnr Bosmansdam & Omuramba Roads Montague Gardens (021) 555 1034 cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.



Manufacturers of Distinctive Decorative Coatings

Creating distinctive cement finishes as you are.