

Cellulose Crack Filler (interior)

Description

A cellulose crack filler for interior use.

Purpose

For filling cracks, gaps round doors, window frames, light switches, knot holes, wood grain, nail holes etc.. Adheres to cement plaster, gypsum plaster, asbestos cement and timber.

Types

One type only.

Site work

Storage

Store in a dry place in a plastic bag sealed with a rubber band.

Surface preparation

Surfaces to be filled must be clean, hard and dry.

Mixing

Mix with clean water to a paste. The larger the fill, the stiffer the paste should be. Usually 2 volumes filler to 1 volume water. Mix only sufficient material for one hour's work.

Application

Fill cracks and holes using a paint scrapper, putty knife or trowel. For filling wood grain, use a brush. Fill slightly proud of the surface, allow filling to dry and harden for about two hours and sandpaper level with surface.

Coverage

Depends on width and depth of joint. Average 5m² per kilogram.

Packaging

Available in 500g, 2kg and 12,5kg paper bags.

Technical Information

Cemcrete provides a free comprehensive technical service based on over 3 decades of experience in the field of surface applications and cement technology.

Head Office
8 Telford Street, Industria
Tel. (011) 474-2415
Fax (011) 474-2416
info@cemcrete.co.za
www.cemcrete.co.za

Gauteng; Mpumulanga
Gareth Beaven
082 566-3107
gareth@cemcrete.co.za

North West Province;
Limpopo; Botswana;
Mozambique
Andre van Eck
083 305-6313
andreve@cemcrete.co.za

Kwa-Zulu Natal; Free State
Dave Rose
082 894-4635
Tel./Fax (031) 903-1374
dave@cemcrete.co.za

Eastern, Western &
Northern Cape; Namibia
Sean Cloete
073 251-4861
Tel. (021) 911-0200
Fax (021) 930-2738
sean@cemcrete.co.za