

Texturite RoughCast

Description

A coloured cement-based decorative finish for exteriors and interiors on walls and ceilings. Integrally coloured to eliminate painting. Permanently hides plaster crazing and other similar defects. Supplied in powder form for mixing on site with clean water. Application is by hand operated Tyrol flicking machine.

Purpose

To provide an exceptionally long lasting coloured, textured coating that hides hair cracks and other imperfections in plaster or concrete.

Types

One type only, but can be used in conjunction with CemBond when application is to smooth or friable surfaces.

Colours

Available in 12 colours.

Applications

Recommended for both interiors and exteriors of homes, offices and factories for walls and ceilings.

Specifying

"Apply in four coats of an approved colour using a handheld flicking machine. The surface to be dry at the time of application and all four coats to be applied on the same day allowing each coat to be dry before applying the next. All completed work to be cured by wetting 3 times with clean water on the day following the day of application. All in accordance with the manufacturer's instructions."

Specimen Finish

A trial area should be treated on-site for the architect's approval.

Suitable Surfaces

Wood-floated cement plaster is recommended, but Texturite Roughcast can be applied to other sound surfaces if used in conjunction with CemBond. Contact our Technical Department for more information.

Site Work

Storage

Store in a dry shed on wooden slats for a maximum of 4 months.

Weather

Do not apply to exteriors if rain is expected or if there is a risk of frost.

Surface preparation

Surfaces should be clean, hard and dry at the time of application. Smooth or friable surfaces should be primed with a solution of 1 volume CemBond and 5 volumes water. This same solution should be used to mix the first coat of Texturite Roughcast.

Masking

Windows, doors and other adjacent surfaces should be masked using masking tape and brown paper. It is important that all coats are applied on the same day and the masking tape removed as soon as the final coat is dry.

Mixing

Medium texture: - 3 volumes Texturite to 1 volume water.
Fine texture: - 2.5 volumes Texturite to 1 volume water.

Application

Place about 1 litre of mixture in the machine. Hold machine about 500mm from wall and spray covering about half the surface with evenly spaced blobs of Texturite. Keep machine moving while spraying. Allow first coat to dry completely, approximately 1 hour. Spray second coat, this time almost obliterating wall with evenly spaced blobs. Again allow to dry completely and apply third coat so that wall is covered. A light fourth coat ensures uniformity of texture and colour.

Curing

Cure by wetting with clean water 3 times during the day following the day of application.

Coverage

One 25kg bag will cover approximately 4 to 7m² depending upon the coarseness of the texture. Less coverage is obtained on ceilings.

Packaging

Supplied in 25kg non-returnable paper bags.

Technical Information

Cemcrete provides a free comprehensive technical service based on over 3 decades of experience in the field of surface applications and cement technology.

Head Office
8 Telford Street, Industria
Tel. (011) 474-2415
Fax (011) 474-2416
info@cemcrete.co.za
www.cemcrete.co.za

Gauteng; Mpumulanga
Gareth Beaven
082 566-3107
gareth@cemcrete.co.za

North West Province;
Limpopo; Botswana;
Mozambique
Andre van Eck
083 305-6313
andreve@cemcrete.co.za

Kwa-Zulu Natal; Free State
Dave Rose
082 894-4635
Tel./Fax (031) 903-1374
dave@cemcrete.co.za

Eastern, Western &
Northern Cape; Namibia
Sean Cloete
073 251-4861
Tel. (021) 911-0200
Fax (021) 930-2738
sean@cemcrete.co.za