

## Crack Filler (exterior)

### Description

A very tough waterproof filler based on special thermoplastic resins and fillers. Softens slightly with increases of temperature, thereby relaxing the tension in the crack.

### Purpose

For filling cracks, gaps round doors, window frames, light switches, knot holes, wood grain, nail holes etc.. Adheres to cement plaster, gypsum plaster and timber.

### Types

One type only.

### Site work

#### Storage

Store in unopened containers for six months. Prevent freezing.

### Application

Fill cracks and holes using a paint scrapper, putty knife or trowel. Fill slightly proud of the surface, allow filling to dry and harden completely, approximately 12 hours, then sand level with surface.

### Coverage

Depends on width and depth of joint. Average 5m<sup>2</sup> per kilogram.

### Packaging

Available in 1,5 and 7,5kg plastic buckets.

### Technical Information

Cemcrete provides a free comprehensive technical service based on over 3 decades of experience in the field of surface applications and cement technology.

Head Office  
8 Telford Street, Industria  
Tel. (011) 474-2415  
Fax (011) 474-2416  
info@cemcrete.co.za  
www.cemcrete.co.za

Gauteng; Mpumulanga  
Gareth Beaven  
082 566-3107  
gareth@cemcrete.co.za

North West Province;  
Limpopo; Botswana;  
Mozambique  
Andre van Eck  
083 305-6313  
andreve@cemcrete.co.za

Kwa-Zulu Natal; Free State  
Dave Rose  
082 894-4635  
Tel./Fax (031) 903-1374  
dave@cemcrete.co.za

Eastern, Western &  
Northern Cape; Namibia  
Sean Cloete  
073 251-4861  
Tel. (021) 911-0200  
Fax (021) 930-2738  
sean@cemcrete.co.za