



ICEMCRETE[®]

Manufacturers of Distinctive Decorative Coatings

CEMBOND

Non-hazardous polymer-based resin

To dispense with hacking when plastering, tiling or painting onto smooth or friable surfaces. It can be used as an adhesive, a bonding liquid for friable surfaces, as a primer for PVA and acrylic paints, as a cement additive to improve adhesion, mixed with cement as a crack filler and mixed with propriety crack fillers to limit “ghosting” of filled spots when over coating with paint. It can be used in plaster mixes to improve the strength and integrity of the plaster and is invaluable for improving the adhesion of cement-based decorative coatings to difficult surfaces.

BENEFITS

- Eliminates hacking
- Sold undiluted, therefore offering a more economical choice. Must be diluted before use
- Lime fast
- Compatible with cement, lime, sand and gypsum
- Dries translucent
- Adheres to concrete, brick, tiles, cement, plaster and stone
- Non-flammable

SPECIFICATIONS

Suitable surfaces	Dry stack brickwork, breeze blocks, stock and face bricks, concrete, hard and clean bag wash, scratch plaster, previously painted surfaces, tiles etc.
Finish	Translucent when dry
Application	Brush-on, sponge-on or roll-on
Packaging	1, 5 & 20 litre containers
Coverage	30m ² / litre of concentrated CemBond mixed 1:5 with water per coat, depending on surface porosity
Curing	Bonding time: ± 1 hour Initial set: ± 4 hours depending on weather Needs to air cure for at least 12 hours
Colour/s	Milky white liquid

