


ICEMCRETE[®]

Manufacturers of Distinctive Decorative Coatings



POOL COPINGS

FINISHES FOR CREATING POOL COPINGS

COLOUR HARDENER

DRY-SHAKE SCREED FLOOR FINISH



A granolithic concrete material that is floated into fresh screed or concrete which colours, strengthens & creates durable surfaces for concrete floors. It is a special blend of cement incorporating very hard-wearing aggregates, light fast pigments & additives which set rock-hard.



Colour Hardener White

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.

COLOUR HARDENER | PRODUCT INFORMATION & USES

SUITABLE SURFACES

New / fresh interior & exterior concrete or screed base.

FINISH

Steel trowel to a smooth finish. Can be textured, stamped or rolled to obtain different tiled or paved effects.

THICKNESS

Depending on screed design - colour penetrates 2 - 3mm into screed.

APPLICATION

Sprinkle-on & trowelled. Can be power floated as well.

CURING

Leave to air cure for 1 day after completion. Damp down with water twice daily for 7 days.

Allow to dry for a minimum of 14 days before sealing.




PACKAGING

20kg bag.

COVERAGE

Approximately 5m² per 20kg bag.


**WATCH
THE VIDEO**
















BENEFITS

- Suitable for interior & exterior floors
- Suitable for domestic or commercial projects
- Colours concrete to a depth of 2 - 3mm (no risk of colour being rubbed off or abraded)
- Extremely durable (dependent on screed mix and curing)
- Can be used in conjunction with SuperScreed (10 - 20mm) where there are height restrictions
 - Can be imprinted
- Can be power floated for large commercial applications



COLOUR HARDENER | COLOUR RANGE



Did you know

Colour Hardener floors should be designed with expansion / control joints incorporated into them, which will minimize the risk of large unsightly cracks when subjected to large changes in temperature, soil or foundation movement etc. Panel sizes should be as symmetrical as possible and should not exceed 9m².

Colour Hardener Grey

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.

DECOCRETE

SHAPEABLE TEXTURED PLASTER



DecoCrete Pink Sandstone with Release Agent

A coloured, cement-based material formulated to be plastered to excessive thicknesses, but does not slide or shrink and dries rock-hard. A textured shaping system for the creation of artistic finishes, such as rock features, imitation brick walls and pool copings.



DecoCrete Machado

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.

SUITABLE SURFACES

Shaped wire mesh (incorporating CemForce), interior & exterior concrete or screed base, interior & exterior wood or steel floated plaster, shaped polystyrene.

FINISH

Steel floated to a smooth finish. Textured to obtain different effects, can be carved with patterns or be imprinted.

THICKNESS

5 - 30mm per coat. When application is to be thicker than 10mm, the material can be pre-mixed with clean river sand to add bulk and texture.

APPLICATION

Steel trowel, hand packed, sponge finished and various other methods.

CURING

Cure by wetting with clean water 3 times on the day following the day of application to ensure hardness & durability. If Release Agent - Pigmented is used, the surface must be washed down after 72 hours curing time & subsequently cured by wetting with clean water.

PACKAGING

40kg bags.
Made to order. Minimum order quantity of 5 x 40kg bags.

COVERAGE

Approximately 1m² if applied 10mm thick.



POOL COPING
DecoCrete Machado



POOL COPING
DecoCrete Greystone with ColourCem Black



ROCK ART
DecoCrete Straw with release agent




IMPRINTING
DecoCrete Greystone



BENEFITS

- Slow setting gives time to work & manipulate the material in-situ
- For use on interior & exterior walls, floors & copings
- Abrasive resistance & coloured throughout
- UV & alkali proof
- Ideal for water features as it can continually be exposed to water




Did you know

DecoCrete can be applied to polystyrene shapes to provide speciality items such as floating rocks or crocodile heads for fish to hide under, or to create rock work or such to compliment dam/pond presentation.

RENOCRETE

VERSATILE SMOOTH / TEXTURED OVERLAY



RenoCrete Sea Foam

A pre-coloured spray-on or trowel-on cement-based polymer modified two-part resurfacing system. RenoCrete beautifies existing surfaces (wall, floor and other) while achieving good compressive, tensile & flexural strength.



RenoCrete Pebble Black

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.

RENOCRETE | PRODUCT INFORMATION & USES

SUITABLE SURFACES

Interior & exterior concrete substrates (floors, pavements, walkways, driveways, pool surrounds & balconies).

FINISH

Sprayed-on / Trowelled-on / Knock-down.

THICKNESS

2 - 3mm.

APPLICATION

Spray-on with a hopper gun or steel trowel.

CURING


In hot dry conditions cure completed work by mist spraying with water 3 times the following day. In light commercial applications it is recommended to densify after 7 days using Cemcrete's Potassium Densifier, prior to sealing.


PACKAGING

20kg bag.

COVERAGE

Approximately 3 - 5m² per 20kg bag, depending on the finish, surface profile, thickness & nozzle settings.
















BENEFITS

- Versatile application; interior & exterior walls, ceilings, floors, counters & vanities
- Suitable for redressing concrete; driveways, walkways, outside patios, pool surrounds & balconies
- Available in multiple finishes, from smooth trowelled to sprayed-on & knock-down
- Achieves good compressive, tensile & flexural strength with abrasion resistance
- UV stable




RENOCRETE | COLOUR RANGE



Final colours for the spray and knock-down applications will vary from the smooth trowelled application. Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.

Did you know

RenoCrete can be applied in various application techniques to achieve different textures and finishes



RenoCrete Pebble Black

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.

EXPOSED AGGREGATE

DECORATIVE AGGREGATE COATING



Exposed Aggregate Cumin

Exposed Aggregate is an 8mm thick exposed stone coating with natural anti-slip properties, which gives a unique and beautiful decorative finish. Ideally suited for external residential & commercial applications where minimum maintenance is required with a decorative finish, such as al fresco areas of retail shops, restaurants & parks, etc.



Exposed Aggregate Cumin

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.

EXPOSED AGGREGATE | PRODUCT INFORMATION & COLOUR RANGE

SUITABLE SURFACES

External floors such as patios, walkways, bomas, pool surrounds, etc.

FINISH

Rough textured exposed stone.

THICKNESS

8mm.

APPLICATION

Trowel-on and washed.

CURING

The panels should be kept covered with plastic for at least 48 hours after application of the retarder, before washing. Refer to the datasheet for full guide.








PACKAGING


20kg bag.

Made to order. Minimum order quantity of 10 x 20kg bags.

COVERAGE

Approximately 0.8m² per 20kg bag, applied at 8mm thick.





BENEFITS

- Aesthetically pleasing
- Easy to clean & maintain
- Durable; abrasion & impact resistant
 - Non-slip & UV stable
- Custom colours available on request

Did you know

Custom colours are easily achieved with the variety of aggregates available. You can also seed larger aggregates for a unique final finish.



0860 CEMCRETE

info@cemcrete.co.za

www.cemcrete.co.za



HEAD OFFICE

Showroom & Warehouse
8 Telford Street
Industria
(011) 474 2415
info@cemcrete.co.za

GAUTENG

Johannesburg Showroom
227 Jan Smuts Avenue
Parktown North
(011) 447 3149
jsa@cemcrete.co.za

Centurion Showroom & Warehouse

15 Coachmen's Park
26 Jakaranda Street
Centurion
(012) 653 6808
pretoria@cemcrete.co.za

CAPE TOWN

Showroom & Warehouse
Unit 3 Eagle Park
cnr Bosmansdam & Omuramba Roads
Montague Gardens
(021) 555 1034
cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.

CEMCRETE[®]

Manufacturers of Distinctive Decorative Coatings

Creating distinctive cement finishes
as *unique* as you are.