

TOUGH WATERPROOF CRACK FILLER

EXTERIOR CRACK FILLER

TOUGH WATERPROOF CRACK FILLER

A very tough waterproof filler based on special thermoplastic resins & fillers. Softens slightly with increase in temperature, thereby relaxing the tension in the crack.

SUITABLE SURFACES

Fills cracks, gaps around doors, window frames, light switches, knot holes, wood grain, nail holes etc. Adheres to cement plaster, gypsum plaster ϑ timber.

APPLICATION Trowel-on.

CURING 12 hours. THICKNESS 1 - 10mm.

PACKAGING 1.5 & 7.5kg containers.

COVERAGE
Depends on width & depth of joint. Average 5m² per kg.

APPEARANCE / COLOUR(S) White.







- 01. Surfaces to be filled must be clean, hard and dry.
- 02. Fill cracks and holes using a paint scraper, putty knife or trowel.
- 03. Allow to dry and harden for two hours & sandpaper level.

0860 CEMCRETE

info@cemcrete.co.za www.cemcrete.co.za











HEAD OFFICE

Showroom & Warehouse & Telford Street Industria (011) 474 2415 info@cemcrete.co.za

GAUTENG

Johannesburg Showroom

227 Jan Smuts Avenue Parktown North (011) 447 3149 jsa@cemcrete.co.za

Centurion Showroom & Warehouse

15 Coachmen's Park 26 Jakaranda Street Centurion (012) 653 6808 pretoria@cemcrete.co.za

CAPE TOWN

Showroom & Warehouse

Unit 3 Eagle Park cnr Bosmansdam & Omuramba Roads Montague Gardens (021) 555 1034 cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.



Creating distinctive cement finishes as you are.