



ICEMCRETE[®]

Manufacturers of Distinctive Decorative Coatings

PRIMERCOTE

TOUGH ADHESIVE FOR NEW SCREEDS

PRIMERCOTE

TOUGH ADHESIVE FOR NEW SCREEDS

Specially designed textured substrate coating used in combination with Cemcrete's FlexBond to bond new screeds to existing surfaces.

SUITABLE SURFACES

Interior & exterior concrete surfaces.

APPLICATION

Brush-on.

CURING

Initial set: 45 - 60 minutes depending on temperatures.

THICKNESS

Minimum thickness at application: 0.8 - 1mm as a slush coat. Maximum thickness at application: 5mm as filler mixed to a paste consistency.

PACKAGING

5 & 20kg containers.

COVERAGE

Approximately 10 - 15m² per 5kg container. Can vary depending on the porosity and texture of the surface.

APPEARANCE / COLOUR(S)

Grey powder.



BENEFITS

- No dilution required, but needs to be mixed with FlexBond
- Will ensure screed adheres to substrate

0860 CEMCRETE

info@cemcrete.co.za

www.cemcrete.co.za



HEAD OFFICE

Showroom & Warehouse
8 Telford Street
Industria
(011) 474 2415
info@cemcrete.co.za

GAUTENG

Johannesburg Showroom
227 Jan Smuts Avenue
Parktown North
(011) 447 3149
jsa@cemcrete.co.za

Centurion Showroom & Warehouse
15 Coachmen's Park
26 Jakaranda Street
Centurion
(012) 653 6808
pretoria@cemcrete.co.za

CAPE TOWN

Showroom & Warehouse
Unit 3 Eagle Park
cnr Bosmansdam & Omuramba Roads
Montague Gardens
(021) 555 1034
cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.

CEMCRETE®

Manufacturers of Distinctive Decorative Coatings

Creating distinctive cement finishes
as *unique* as you are.