

PIGMENTED POWDER RELEASE AGENT

# RELEASE AGENT

## PIGMENTED POWDER RELEASE AGENT

To be used in conjunction with Colour Hardener to provide colour contrast 8 ensure that the mould releases cleanly when imprinting the surface of Colour Hardener. It may also be used in conjunction with many other decorative coatings from Cemcrete, when imprinting is done.

#### SUITABLE SURFACE

Colour Hardener, DecoCrete, SatinCrete, RenoCrete; use with imprinting mats.

APPLICATION Dry shake.

### **CURING**

After application Release Agent should be left on the imprinted surface for at least 72 hours to set. Thereafter rinse with clean water to remove excess material.

PACKAGING 5 & 15kg containers.

COVERAGE Approximately 300g/m<sup>2</sup>

APPEARANCE / COLOUR(S) Coloured powder.






Terracotta

















- 01. Dust Release Agent onto the imprint mat. This will ensure that the mat doesn't stick to the surface. Place the mat carefully onto the surface. Stamp the imprint mat to transfer the texture onto the surface.
- 22. Remove the imprint mat carefully.
  After 3 days wash surface to remove excess Release Agent.
- 03. Finished sealed floor.







### Centurion Showroom & Warehouse

15 Coachmen's Park 26 Jakaranda Street Centurion (012) 653 6808 pretoria@cemcrete.co.za

## **CAPE TOWN**

#### Showroom & Warehouse

Unit 3 Eagle Park cnr Bosmansdam & Omuramba Roads Montague Gardens (021) 555 1034 cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.



Creating distinctive cement finishes we as you are.