



FIBRE-CEMENT CASTING MIX

TEXCRETE FIBRE-CEMENT CASTING MIX

A thixotropic, quick setting, enhanced fibre-cement blend. Mixed with a solution of FlexBond for the saturation and impregnation of CemForce to form a reinforced product that can be cast into latex or silicone moulds. Produces castings of about 4 to 8 mm in thickness.

SUITABLE SURFACES Wood, rubber, latex, perspex or cardboard moulds

APPLICATION Pouiring into mould.

CURING

First allow work to completely dry out before immersing or wetting down with water. The longer this second wetting is carried out, the better the strengths achieved.

THICKNESS 4-8mm. PACKAGING 20kg bags.

COVERAGE 20kg of TexCrete will cover approximately $0.75 m^2$ when applied 5mm thick.

APPEARANCE / COLOUR(S) Available in light colours like Ivory and Straw TexCrete can be coloured in powder form with ColourCem Or CreteStain can be used to add colour to TexCrete once dry.



BENEFITS

- Moulding of lightweight small and large intricate castings where fine surface definition is required - Can also be applied onto a layer of CemForce to create positive work, instead of casting into moulds 0860 CEMCRETE info@cemcrete.co.za www.cemcrete.co.za

f 🖸 🦻 in 🛗

HEAD OFFICE

Showroom & Warehouse 8 Telford Street Industria (011) 474 2415 info@cemcrete.co.za

GAUTENG

Johannesburg Showroom 227 Jan Smuts Avenue Parktown North (011) 447 3149 jsa@cemcrete.co.za

Centurion Showroom & Warehouse 15 Coachmen's Park 26 Jakaranda Street Centurion (012) 653 6808 pretoria@cemcrete.co.za

CAPE TOWN

Showroom & Warehouse Unit 3 Eagle Park cnr Bosmansdam & Omuramba Roads Montague Gardens (021) 555 1034 cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.



Creating distinctive cement finishes

as you are.

as un