

ICEMCRETE[®]

Manufacturers of Distinctive Decorative Coatings



THATCHCRETE

CEMENT LINING FOR THATCH ROOFS

THATCHCRETE

CEMENT LINING FOR THATCH ROOFS

For creating a thin, reinforced, waterproof cement lining that is a low conductor of electricity and can be applied directly onto the exterior of an old or new combed grass-thatched roof. This lining is tough enough to resist mammals and birds from causing damage to the roof or entering the building.

SUITABLE SURFACES

Exterior of an old or new combed grass-thatched roof.

FINISH

Textured finish.

THICKNESS

Approximately 4 - 5mm depending on thatch density & profile.

APPLICATION

Brush-on.

CURING

Allow finished ThatchCrete work to air cure for 5 days.

PACKAGING

40kg bags.

COVERAGE

Approximately 4m² for 3 coats per 40kg bag depending on number of layers of CemForce used and surface profile.

NOTE

Can be coated with TPC Roof Paint, or CemWash for various colour and finish options.



BENEFITS

- Applied directly onto the exterior of new or old combed grass-thatched roofs
- Low conductor of electricity
- Waterproof
- Resistant to dismantling by mammals (such as baboons, etc) & birds



0860 CEMCRETE
info@cemcrete.co.za
www.cemcrete.co.za



HEAD OFFICE

Showroom & Warehouse
8 Telford Street
Industria
(011) 474 2415
info@cemcrete.co.za

GAUTENG

Johannesburg Showroom
227 Jan Smuts Avenue
Parktown North
(011) 447 3149
jsa@cemcrete.co.za

Centurion Showroom & Warehouse

15 Coachmen's Park
26 Jakaranda Street
Centurion
(012) 653 6808
pretoria@cemcrete.co.za

CAPE TOWN

Showroom & Warehouse
Unit 3 Eagle Park
cnr Bosmansdam & Omuramba Roads
Montague Gardens
(021) 555 1034
cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.

CEMCRETE[®]

Manufacturers of Distinctive Decorative Coatings

Creating distinctive cement finishes
as *unique* as you are.