

# Floorseal Stripper Datasheet

March 2014

Page 1 of 2

Cemcrete's **Floorseal Stripper** is a liquid sealer stripper which is opaque in appearance and has a strong odour.

## Purpose

**Floorseal Stripper** is used to remove acrylic sealers like Colour Hardener Sealer from decorative and or plain concrete floors, driveways and pathways. Do not apply to any CreteCote floors as the stripper may cause softening of the decorative coating.

## Application

Ideally suited for domestic or commercial floor coverings requiring minimum maintenance.

## Types

Available in one type only.

## Specifying

Apply **Floorseal Stripper** as per manufacturers instructions. Repeat as necessary.

## Limitations

Contains solvent which evaporates rapidly. Once solvent has evaporated the stripping process will stop. Cannot be used on frozen surfaces or in freezing conditions. **Floorseal Stripper** will not remove hardened sealer completely from porous surfaces.

## Applications

Recommended for the removal of Cemcrete's Colour Hardener Sealer.

## Suitable surfaces

Concrete surfaces previously sealed with acrylic sealer. Test the stripper on a small inconspicuous area before general application.

## Site Work

Keep lid tightly closed when not in use and keep in a cool place out of direct sunlight.

## Storage

Can be stored in cool, dry conditions above 5°C away from direct sunlight in properly sealed steel drums for up to six months. After this time, product should be checked to ensure it's suitability for use. Store away from foodstuffs.

## Weather

Do not apply when the temperature is below 5°C nor on frozen surfaces. For best results use in temperatures between 15 – 25°C.

## Surface preparation

Surfaces should be lightly sanded with 60 or 80 grit sandpaper before application of the stripper to assist solvent penetration.

## Mixing

Shake well before use. Use straight from the can, no dilution required.

## Masking

For best results all doors and adjacent surfaces should be masked using masking tape and brown paper. All masking material must be removed at the end of a day's work.

Cemcrete provides a comprehensive technical service based on over 4 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.

# Floorseal Stripper Datasheet

**March 2014****Page 2 of 2**

---

**Application**

Apply liberally straight from the can using a large paint brush. Allow to stand for approximately 15 minutes, then scrub the surface using a floor buffing pad or a household scrubbing brush to break down the sealer. Mop and rinse with water to remove from surface. Should any sealer remain, repeat the above. Ensure rinse water and run off is collected and disposed of in accordance with local authority requirements. Avoid contact with skin and eyes. Avoid breathing vapour. Do not smoke while using this product. Must wear protective mask and goggles when handling this product. Open lid slowly to release pressure build up. Use only in well ventilated areas.

---

**Coverage**

Approximately 5-6m<sup>2</sup> per litre per coat depending on thickness and surface.

---

**Packaging**

In 1 litre and 5 litre non-returnable steel containers.

Cemcrete provides a comprehensive technical service based on over 4 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.

---

**Johannesburg Head Office**

8 Telford Street  
Industria  
011 474 2415

**Johannesburg Showroom**

227 Jan Smuts Avenue  
Parktown North  
011 447 3149

**Centurion Showroom & Warehouse**

15 Coachmen's Park  
26 Jakaranda Street, Centurion  
012 653 6808

**Cape Town Showroom & Warehouse**

Eagle Park, cnr Bosmansdam &  
Omuramba Roads, Montague Gardens  
021 555 1034