

The logo for ICEMCRETE, featuring the word "ICEMCRETE" in a bold, red, sans-serif font. The letter "I" is stylized with a black vertical bar to its left. A registered trademark symbol (®) is located at the top right of the word.

ICEMCRETE®

Manufacturers of Distinctive Decorative Coatings

A close-up photograph showing a person's hand using a blue-handled trowel to apply a thick, greyish-brown plaster to a wall. The plaster is being smoothed over a wooden board. The background shows a finished, light-colored wall.

PLASTERCOTE

Thin, Leveling Plaster For Walls

A specially designed cement-based plaster mixture for rapid thin application to brickwork and blockwork to fill the joints and other imperfections economically. To provide a level base for the application of Cemcrete's SatinCrete, CemCote, CemWash, Thermoplastic Coating, StippleCrete and Texturite Roughcast to walls constructed with bricks or blocks.

BENEFITS

- Dispenses with expensive conventional plastering
- Easy to use
- Good filling capacity
- Recommended for affordable housing to dispense with expensive conventional plastering
- Used as a levelling base coat for the final finishing coat

SPECIFICATIONS

Suitable surfaces	Walls constructed with bricks or blocks. Previously coated walls
Finish	Smooth
Thickness	Minimum thickness application - Scrape coat designed as filler Maximum thickness application - 2mm
Application	Trowel-on
Packaging	40kg bags
Coverage	Approximately 10m ² per 40kg if not exceeding 2mm thick and 1.5 litre concentrated CemBond
Curing	Cure all completed PlasterCote by wetting with clean water three times the next day Wait a minimum of 14 days before applying your final coating
Colour/s	Grey

