

The logo for ICEMCRETE, featuring the word "ICEMCRETE" in a bold, red, sans-serif font. The letter "I" is stylized with a black vertical bar on its left side. A registered trademark symbol (®) is located at the top right of the word.

ICEMCRETE[®]

Manufacturers of Distinctive Decorative Coatings








ROOFSEAL

Membrane System For Waterproofing Roofs

To provide an extremely durable, easy-to-apply membrane system for concrete roofs, fibre cement and cement tiles. Although essentially a roof paint, it also has other applications such as side cladding, previously painted galvanized roofs, parapet walls and the sealing of roof/gutter bolts.

BENEFITS

- Waterproof, very durable and UV light resistant
- Easy-to-apply waterproof membrane system for concrete roofs



SPECIFICATIONS

Suitable Surfaces	Concrete, bituminous felt, timber, galvanized iron, asbestos cement and foam cement
Finish	Smooth matt finish
Thickness	When used with the membrane 3mm per coat
Application	Brush-on
Packaging	1, 5 & 20 litre containers
Coverage	0.5m ² / litre for full application of 3 coats
Curing	Allow the polyester / RoofSeal sandwich to dry out for 3 or 4 days, depending on the weather, and apply a final finishing coat of RoofSeal
Colour/s	Available in 6 colours

INTENDED FOR USE WITH

RoofSeal Acrylic Primer	1, 5 & 20 litre containers - 5m ² / litre
Polyester Membrane	1m wide, up to 150mm in length

TOOLS NEEDED

Brush
Roller
Broom