

# Slip Resistant Additive Datasheet

September 2018

Page 1 of 1

White fine granules.

## Purpose

To increase the slip resistance of sealers on floors.

## Advantages

- Disperses readily and evenly through sealer.
- Slow to settle or float in sealer.
- Polymeric in nature, therefore, more compatible physically with sealers eg. expansion / contraction.
- Generally increases abrasion resistance of sealers.
- Compatible with solvent and water based systems.
- Does not detract from aesthetic appeal of most decorative surface. In some cases enhances appearance.

## Preparation

Prior to sealing, mix the required amount of the selected slip reducer into the final coat of sealer. Ensure sealer is applied using a suitable roller. Extend the final sealer coat thinly to ensure the texture created by the slip reducing additive is visual. The coverage will depend on texture. Some settling or flotation can occur, therefore, stir mix periodically (2 minute intervals).

## Limitations

- If left in some solvent type sealer for extended period (>4 hours). There is a tendency for swelling and sticking together of particle.
- As with most materials it will slowly wear, hence periodic check of slip resistance is advisable.
- May dull gloss retention.

## Coverage

Depends on type of sealer used. Refer to its datasheet.

## Packaging

Supplied in bags of 18g's and 90g's.

## Manufacturer's Warranty

Cemcrete warrants that the products manufactured by it shall be free from material defects and will be consistent with its normal high quality. Should any of the products be proven defective, the liability to Cemcrete shall be limited to replacement of the product ex-factory. Cemcrete makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties expressed or implied. The user shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith.

Cemcrete provides a comprehensive technical service based on over 3 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.

### Johannesburg Head Office

8 Telford Street  
Industria  
011 474 2415

### Johannesburg Showroom

227 Jan Smuts Avenue  
Parktown North  
011 447 3149

### Centurion Showroom & Warehouse

15 Coachmen's Park  
26 Jakaranda Street, Centurion  
012 653 6808

### Cape Town Showroom & Warehouse

Eagle Park, cnr Bosmansdam &  
Omuramba Roads, Montague Gardens  
021 555 1034