

**CEMCRETE**<sup>®</sup>

Manufacturers of Distinctive Decorative Coatings



TEXCRETE

---

Fibre-cement casting mix



A thixotropic, quick setting, enhanced fibre-cement blend. Mixed with a solution of FlexBond for the saturation and impregnation of CemForce to form a reinforced product that can be cast into latex or silicone moulds. Produces castings of about 4 to 8 mm in thickness.

## BENEFITS

- Moulding of lightweight small and large intricate castings where fine surface definition is required
- Can also be applied onto a layer of CemForce to create positive work, instead of casting into moulds

## SPECIFICATIONS

Suitable surfaces	Wood, rubber, latex, perspex or cardboard moulds
Finish	Will pick up the texture of the mould
Thickness	4-8mm
Application	Brush-on or spray-on
Packaging	40kg bags
Coverage	40kg of TexCrete will cover approximately 1.5m <sup>2</sup> when applied 5mm thick
Curing	First allow work to completely dry out before immersing or wetting down with water. The longer this second wetting is carried out, the better the strengths achieved
Colour/s	Available in light colours like Ivory and Straw. TexCrete can be coloured in powder form with ColourCem. Or CreteStain can be used to add colour to TexCrete once dry.

## INTENDED FOR USE WITH

FlexBond	1, 5 and 20 litre plastic containers
CemForce	1m width with any length
Glass Fibre Mesh	1m widths up to 50m lengths
CreteStain	125ml, 1 litre and 25 litre non-returnable containers - approximately 8m <sup>2</sup> /litre/coat

## TOOLS NEEDED

Brush  
Low-pressure spray  
Trowel

## SUPPORTING CEMCRETE PRODUCTS

CreteStain  
ColourCem  
Colour Hardener Sealer

